

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054656 A1

(51) International Patent Classification⁷: **F02M 5/02**,
55/00, 57/02

[GB/GB]; The Old Vicarage, Rockness, Horsley, Stroud
GL6 0PJ (GB). **MALE, Andrew** [GB/GB]; 106, Carlton
Road, Walton on Thames KT12 2DQ (GB).

(21) International Application Number:
PCT/GB2003/004739

(74) Agents: **KELTIE, David, Arthur et al.**; David Keltie As-
sociates, Fleet Place House, 2 Fleet Place, London EC4M
7ET (GB).

(22) International Filing Date:
4 November 2003 (04.11.2003)

(81) Designated States (*national*): JP, US.

(25) Filing Language: English

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): **DELPHI
TECHNOLOGIES, INC.** [US/US]; P.O. Box 5052, Troy,
MI 48007 (US).


Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **KNIGHT, Andrew**

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: ACCUMULATOR FUEL SYSTEM



(57) Abstract: An accumulator fuel system for an internal combustion engine having a plurality of engine cylinders, includes an accumulator fuel volume (12; 112) for supplying high pressure fuel to one or more of a plurality of injectors (10) of the fuel system, each of which is arranged to supply fuel to an associated one of the engine cylinders. The accumulator fuel volume (12; 112) is integrated within an engine component, where the engine component provides a purpose other than that solely of an accumulator volume for storing high pressure fuel. For example, the accumulator volume (12; 112) is defined in one embodiment within a rocker shaft (32) of the engine and in another embodiment within the engine cylinder head (16).

WO 2005/054656 A1